

## PRODUCT DESCRIPTION

**Oscar MTF OEM Specific Haldex** is a specially formulated synthetic transmission oil developed for Haldex couplings of all generations. It is a fully synthetic gear lubricant formulated from synthetic base oils and an advanced additives system.

## APPLICATION

Oscar MTF OEM Specific Haldex provides excellent low temperature fluidity for safe lubrication during very low temperature transmission. Recommended for use in AUDI, VOLKSWAGEN, SEAT, SKODA, OPEL, LANDROVER and VOLVO all-wheel drive vehicles equipped with Haldex, Allroad, Quattro and 4motion couplings where compliance with the requirements of VW G 060 175 A2 is required.

## PROPERTIES

- Exceptional thermal stability
- Enhanced frictional properties
- Resistance to high temperature oxidation
- Outstanding protection against low speed/high torque wear

## PERFORMANCE LEVELS

Meets and exceeds:

VW G 060 175 A2; VW G 055 175 A2; VW G 052 175 A2; BMW 8322 2413513; Volvo 31367940; Opel 1940057; VAUXHALL 1940057; GM 93165387

## TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	MTF OEM Specific Haldex
Density @ 15°C, kg/l	ASTM D1298	kg/l	0.85
Viscosity @ 100°C, cSt	ASTM D445	cSt	5.7
Viscosity @ 40°C, cSt	ASTM D445	cSt	27.5
Viscosity Index (min)	ASTM D2270	-	155
Pour Point, °C	ASTM D97	°C	-48 min.
Flash Point, °C	ASTM D92	°C	230

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice

## HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.oscarlubricants.com](http://www.oscarlubricants.com)