

## PRODUCT DESCRIPTION

**Oscar MTF SAE 75W85 API GL-4** is a fully synthetic gear lubricant formulated from synthetic base oils and an advanced additive system.

## APPLICATION

Oscar MTF SAE 75W85 API GL-4 provides excellent low temperature fluidity for safe lubrication during very low temperature transmission and transaxle startup, and also maintains a thick protective oil film during extremely hot operating conditions. Used in all synchronized and non-synchronized manual transmission types operating under heavy loads and at high speed in extremely low temperatures, where an API GL-4 and MT-1 oil is required.

## PROPERTIES

- Exceptional thermal stability
- Enhanced frictional properties
- Resistance to high temperature oxidation
- Outstanding protection against low speed/high torque wear

## PERFORMANCE LEVELS

Meets and exceeds:

API GL-4; API MT-1; MIL L 2105; MB 235.31

## TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	Oscar MTF
Viscosity Grade			75W85
Density @ 15°C, kg/l	ASTM D1298	kg/l	0.88
Viscosity @ 100°C, cSt	ASTM D445	cSt	11.8
Viscosity @ 40°C, cSt	ASTM D445	cSt	69.5
Viscosity Index (min)	ASTM D2270	-	165
Pour Point, °C	ASTM D97	°C	-42
Flash Point, °C	ASTM D92	°C	210

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice

## HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.oscarlubricants.com](http://www.oscarlubricants.com)