

PRODUCT DESCRIPTION

High-performance additive for stabilizing the viscosity of motor oils. Offers protection against mechanical shear losses to the oil under extreme running conditions and is effective against the thinning of motor oils due to frequent cold starts.

AREAS OF APPLICATION

For all passenger vehicles and commercial vehicles, gasoline and diesel engines in new and used vehicles.

APPLICATION

Can contents (300 ml) are sufficient for 5 liters of motor oil. After adding to the motor oil, allow the engine to run warm. The product can be added at any time.

PROPERTIES

- stabilizes loss of viscosity
- compatible with mineral and synthetic oils
- reduces engine noise
- optimum oil pressure under all operating conditions
- reduces oil consumption
- improves the movable seal between piston and cylinder
- reduces wear

TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	OIL VISCOSITY TREATMENT
Color / appearance		-	brown
Density at 20 °C	DIN 51757	g/cm ³	0.889
Viscosity at 20 °C	DIN 51377	mPas	2,400
Flash point	DIN ISO 2592	°C	Min. 100
Pour point	DIN ISO 3016	°C	-5
Odor	-	-	characteristic
Form	-	-	liquid

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.oscarlubricants.com