

## PRODUCT DESCRIPTION

Oscar Jade Optimum 5W40 C2 C3 is a very high performance, **fully synthetic MID SAPS** lubricant for gasoline and diesel engines, including the ones complying with **ACEA C2/C3** standard. Oscar Jade Optimum is formulated to reduce pollutant emissions, such as HC, NOx, CO and particles and to protect and ensure longevity of post treatment anti-pollution systems, such as particulate filters (GPF, DPF) and three-way catalysts. Oscar Jade Optimum also helps to lengthen the engine life thanks to its excellent resistance to temperature variations and permits an extra-long oil change interval.

## APPLICATION

This product meets or exceeds the requirements of the latest API and ACEA industry specifications for petrol engine oils, as well as the requirements of many major American, and European engine manufacturers. Suitable for use in both gasoline and diesel passenger cars and light commercial vehicles.

## PROPERTIES

- Protects engines from wear and deposit build-up
- **LSPI protection**
- **Fuel Economy**
- **GPF, DPF protection**

## PERFORMANCE LEVELS

Meets and exceeds: ACEA C2/C3 (A3/B4 backward compatible); API SN; API SN Plus; MB 229.31/229.51; BMW LL04; dexos 2; Porsche A40; Renault RN0700; Renault RN0710; VW 502.00/505.00; Fiat 9.55535-S2; Ford WSS-M2C917-A; PSA B71 2296

## TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	OSCAR JADE OPTIMUM 5W40 C2 C3
Viscosity Grade			5W40
Density @ 15°C	ASTM D1298	kg/l	0.855
Viscosity @ 100°C	ASTM D445	cSt	14.5
Viscosity @ 40°C	ASTM D445	cSt	90
Viscosity Index (min)	ASTM D2270	-	170
Cold Crank Simulator	ASTM D5293	cP	<6,600 @ -30 °C
HTHS Viscosity 150°C	-	mPa.s	3.50
Pour Point	ASTM D97	°C	-39
Flash Point	ASTM D92	°C	230
Total Base Number (TBN)	ASTM D2896	mg KOH/g	8

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice

## HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website [www.oscarlubricants.com](http://www.oscarlubricants.com)