

## PRODUCT DESCRIPTION

**Oscar Jade 2T Outboard TC-W3** is a high quality two stroke engine lubricant that delivers excellent performance in water-cooled and air-cooled applications. It is formulated to provide excellent lubrication and deposit control in a wide range of applications.

## APPLICATION

Recommended for use in two-stroke engines where TC-W3 or earlier general-purpose lubricants are recommended. These applications include outboard engines, motorcycles, lawn mowers, scooters, golf carts, chain saws, and other two-stroke powered equipment.

## PROPERTIES

- Exceptionally clean engines
- Excellent rust protection
- Long spark plug life
- Easy mixing and stable mixtures with gasolines

## PERFORMANCE LEVELS

Meets and exceeds:

API TC for gasoline engines air cooled 2 strokes (20 to 500 c.c.).

NMMA TC-W3 for gasoline engines water cooled 2 strokes.

## TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	OSCAR JADE 2T OUTBOARD
Viscosity Grade			-
Density @ 15°C	ASTM D1298	kg/l	0.876
Viscosity @ 100°C	ASTM D445	cSt	8.1
Viscosity @ 40°C	ASTM D445	cSt	47.9
Viscosity Index (min)	ASTM D2270	-	142
Pour Point	ASTM D97	°C	-44
Flash Point	ASTM D92	°C	171
Total Base Number (TBN)	ASTM D2896	KOH/g	10.2

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice

## HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website [www.oscarlubricants.com](http://www.oscarlubricants.com)