

## PRODUCT DESCRIPTION

**Oscar ATF Type A** is multipurpose automatic transmission fluid for use in automatic gear boxes and power steering systems of vehicles where Type A suffix A is recommended.

## APPLICATION

Automatic transmissions in certain older cars and for the makeup and refill in power steering systems.

## PERFORMANCE LEVELS

Meets and exceeds:

- Meets the requirements of ATF (Automatic Transmission Fluid)  
Meets the requirements of General Motor's Type A Suffix A

## TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	ATF TYPE A
Viscosity Grade			-
Density @ 15°C, kg/l	ASTM D1298	kg/l	0.863
Viscosity @ 100°C, cSt	ASTM D445	cSt	7.5
Viscosity @ 40°C, cSt	ASTM D445	cSt	35.2
Viscosity Index (min)	ASTM D2270	-	≥ 160
Brookfield Viscosity @-40 °C, cP	ASTM D2983	cP	<50,000
Pour Point, °C	ASTM D97	°C	-42
Flash Point, °C	ASTM D92	°C	>185

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice

## HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website [www.oscarlubricants.com](http://www.oscarlubricants.com)