



# PRODUCT DATA SHEET

## Oscar UTTO SAE 80W

### DESCRIPTION

Oscar UTTO SAE 80W is an extra high-performance, heavy-duty transmission and drive-train lubricants engineered to meet or exceed the requirements of the rigorous Caterpillar TO-2 specification. This product line is uniquely designed to optimize the performance of powershift transmissions, gearboxes, and final drives. In hydraulic applications, they provide maximum protection even in high pressure systems

### PROPERTIES

This lubricant assures:

- Optimized clutch-friction retention and slippage control
- Increased levels of anti-wear and load carrying capability
- Reduced gear wear and extended life in transmissions, gearboxes, and final drives
- Outstanding hydraulic oil stability and protection against high-pressure pump wear

### APPLICATIONS

- Heavy duty transmissions, gear boxes, final drives, and hydraulic systems used in off-highway applications
- Off-highway industries including: mining, construction, quarrying, and agriculture
- Manual, powershift, and automatic transmissions where Allison C-4 fluids are called for including Twin Disc and transmissions calling for Type F fluids
- Most mobile equipment hydraulic applications

Meets the requirements of: SAE 80W, ISO VG 46, API GL-4, HLP-D/HVLP-D (ISO VG 46-68), DENISON HF-0, HF-1, HF-2, SPERRY VICKERS I-286-S, M-2950-S, ALLISON C4, MIL-L-2105, CATERPILLAR TO-2, ZF TE-ML 05F, 17E, ALLISON C3, CASE MS-1204, MS-1205,MS-1206,MS-1207,MS-1209,MS-1210, CASE NEW HOLLAND MAT 3525, 3505, DEUTZ Hydraulic Trans Fluid, DENISON HF 1/2/3, JOHN DEERE J 20C/D, MASSEY FERGUSON M-1110, M-1127 A, B; M-1129 A; M-1135; M-1139; M-1141; M-1143; M-1145, VALMET/VOLVO BM, ZF TE-ML 03E/06

### TYPICAL PROPERTIES

Oscar MTF		
Typical Properties	SAE Grade	80W
	Performance	TO-2
Test Parameters	ASTM Method	Typical Values
Density @ 15°C, kg/l	ASTM D1298	0.88
Viscosity @ 100°C, cSt	ASTM D445	9.8
Viscosity @ 40°C, cSt	ASTM D445	55
Viscosity Index	ASTM D2270	160
Flash Point, °C	ASTM D92	232
Pour Point , °C	ASTM D97	-38

February 2021

*The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice.*