



# PRODUCT DATA SHEET

## Oscar UTTO 10W30

### DESCRIPTION

Oscar UTTO 10W30 is a super high-performance multifunctional transmission lubricant for construction machinery.

### PROPERTIES

This lubricant assures:

- highest pressure-absorption capability
- wear reduction
- noise reduction
- excellent viscosity/temperature properties
- excellent ageing resistance
- all sealing materials compatibility

### APPLICATIONS

Used in powered transmission and axle drives, especially for high-load hypoid gearings. Not to be used as engine oil.

Meets the requirements of: API GL 4, Case New Holland MAT-3525, M2C-134 A-D, FNHA-2-D.201.00, John Deere JDM-J20C, Massey-Ferguson M1143, M1145, Volvo WB 101, Transmission Oil 97303:015, ZF TE-ML 03E, 05F, 06D, 06K, 06M, 06N, 06R, 17E, 21F, Caterpillar TO-4

### TYPICAL PROPERTIES

Oscar UTTO		
Typical Properties	SAE Grade	10W30
Test Parameters	Performance	GL-4
Test Parameters	ASTM Method	Typical Values
Density @ 15°C, kg/l	ASTM D1298	0.870
Viscosity @ 100°C, cSt	ASTM D445	10.50
Viscosity @ 40°C, cSt	ASTM D445	69
Viscosity Index	ASTM D2270	135
Flash Point, °C	ASTM D92	230
Pour Point, °C	ASTM D97	-25

August 2020

*The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice.*