



PRODUCT DATA SHEET

Oscar UTTO 15W30

DESCRIPTION

Oscar UTTO 15W30 is a super high-performance multifunctional transmission lubricant for construction machinery.

PROPERTIES

This lubricant assures:

- highest pressure-absorption capability
- wear reduction
- noise reduction
- excellent viscosity/temperature properties
- excellent ageing resistance
- all sealing materials compatibility

APPLICATIONS

Used in powered transmission and axle drives, especially for high-load hypoid gearings. Not to be used as engine oil.

Meets the requirements of: API GL 4, Allison C-4; Ford ESN M2C 86B, C, Ford ESN M2C 134-D; Massey Ferguson M1135, M1141, M1143, M1145; NEW HOLL. FNHA-2-C-201.00; ZF TE-ML 03E, 05F, 06K, 17E, 21F quality

TYPICAL PROPERTIES

Oscar UTTO		
Typical Properties	SAE Grade	15W30
Test Parameters	Performance	GL-4
Test Parameters	ASTM Method	Typical Values
Density @ 15°C, kg/l	ASTM D1298	0.885
Viscosity @ 100°C, cSt	ASTM D445	10.90
Viscosity @ 40°C, cSt	ASTM D445	65.6
Viscosity Index	ASTM D2270	140
Flash Point, °C	ASTM D92	220
Pour Point, °C	ASTM D97	-30

July 2021

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice.