



PRODUCT DATA SHEET

Oscar GEO 15W40

DESCRIPTION

Premium CNG/LNG oil formulated to deliver outstanding protection and long drain performance in a wide variety of compressed natural gas (CNG), liquefied natural gas (LNG) and liquefied petroleum gas (LPG) engine applications

PROPERTIES

This lubricant assures:

- Alternative fuel performance:
- Great performance for medium and heavy duty vehicles using CNG, LNG or LPG.
- Excellent engine cleanliness
- Sludge control; and valve, or piston deposits in field trials and engine tests.
- Oil oxidation/nitration control

APPLICATIONS

Wide variety of compressed natural gas (CNG), liquefied natural gas (LNG) and liquefied petroleum gas (LPG) engines

TYPICAL PROPERTIES

Oscar Zircon Starlight		
Typical Properties	SAE Grade	15W40
	API level	CI-4/SL
Test Parameters	ASTM Method	Typical Values
Density @ 15°C, kg/l	ASTM D1298	0.87
Viscosity @ 100°C, cSt	ASTM D445	15.8
Viscosity @ 40°C, cSt	ASTM D445	126
Viscosity Index	ASTM D2270	132
Flash Point, °C	ASTM D92	230
BN, mg KOH/g	ASTM D2896	6
Pour Point, °C	ASTM D97	-27

October 2017

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice.