



PRODUCT DATA SHEET

Oscar GEO 40

DESCRIPTION

Premium CNG/LNG oil formulated to deliver outstanding protection and long drain performance in a wide variety of compressed natural gas (CNG), liquefied natural gas (LNG) and liquefied petroleum gas (LPG) stationary engine applications

PROPERTIES

This lubricant assures:

- Alternative fuel performance:
- Great performance for medium and heavy-duty engines using CNG, LNG or LPG.
- Excellent engine cleanliness
- Sludge control; and valve, or piston deposits in field trials and engine tests.
- Oil oxidation/nitration control

APPLICATIONS

Wide variety of compressed natural gas (CNG), liquefied natural gas (LNG) and liquefied petroleum gas (LPG) engines

TYPICAL PROPERTIES

Oscar Zircon Starlight		
Typical Properties	SAE Grade	40
	API level	CF
Test Parameters	ASTM Method	Typical Values
Density @ 15°C, kg/l	ASTM D1298	0.880
Viscosity @ 100°C, cSt	ASTM D445	13.5
Flash Point, °C	ASTM D92	255
BN, mg KOH/g	ASTM D2896	5.5
Pour Point, °C	ASTM D97	-25

October 2018

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice.