

Oscar HDM Air Tool Lubricant 46

PRODUCT DESCRIPTION

Oscar HDM Air Tool Lubricants is a mineral mixture of specially selected base oils combined with antiwear and extreme-pressure additives but also additives to improve anti-rust, and an emulsifier to absorb moisture.

APPLICATION

Used for the lubrication of pneumatic tools controlled by compressed air, for example drilling equipment.

PROPERTIES

- Resistance to rust and wear
- Extreme pressure properties
- Good demulsibility
- Protect components against corrosion.

PERFORMANCE LEVELS

Meets the requirements of DIN 51502 D and ISO 6743-11 Class LP

TYPICAL PROPERTIES

Oscar HDM Air Tool Lubricant 46		
Density @ 15°C, kg/l	ASTM D1298	0.88
Viscosity @ 40°C, cSt	ASTM D445	46
Viscosity @ 100°C, cSt	ASTM D445	7.5
Viscosity Index	ASTM D2270	128
Flash point, °C	ASTM D92	Min 230
Pour Point, °C	ASTM D97	-25

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.oscarlubricants.com