

Oscar HDM HydraXP ZF HVI

PRODUCT DESCRIPTION

OSCAR HDM HydraXP ZF HVI – zinc- and ash-free, demulsifying and universally high viscosity index hydraulics oils

Oscar HDM HydraXP ZF HVI are zinc- and ash-free, demulsifying and universally usable hydraulic and industrial gear oils of the latest generation with excellent ageing stability, outstanding wear protection (FZG A/8.3/90: >12) and high corrosion protection. OSCAR HYDRA XP ZF HVI oils fulfill and surpass the requirements on hydraulic oils acc. to DIN 51524-3; ISO 6743/4, HV ISO 11158, HV. Denison HF0, HF1, HF2

APPLICATION

Every industrial lubricant recommendation should be done after an expert consultation on the application in question. Only then the best lubricant can be selected. Oscar HDM hydraulic oils series “HydraXP” are fitted to all your industrial applications.

Oscar HDM Hydra XP ZF HVI oils are high grade products, which can be used in all hydraulic systems. Oscar HDM HydraXP products are recommended for use in machine tools where contact between hydraulic fluids and metalworking oils can take place.

Available in VG 10, 22, 32, 46, 68, 100, 150.

PERFORMANCE LEVELS

Fulfill and surpass the minimum demands of DIN 51524-3; ISO 6743/4, HV ISO 11158, HV. Denison HF0, HF1, HF2

TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	OSCAR HDM HYDRA XP ZF HVI				
Product Name	-	-	15	32	46	68	100
Density at 15 °C, kg/m ³	ASTM D1298	kg/m ³	859	871	879	882	885
Flash point Cleveland, °C	ASTM D92	°C	180	178	186	210	240
Kinematic viscosity at 40 °C, mm ² /s	ASTM D445	mm ² /s	15	32	46	68	100
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	mm ² /s	3.8	6.3	8.1	11.0	14.5
Viscosity Index	ASTM D2270	-	151	152	149	154	150
Pour point, °C	ASTM D97	°C	-43	-41	-40	-39	-38

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.oscarlubricants.com