

OSCAR HDM PYROX SYN Complex Moly EP 0

PRODUCT DESCRIPTION

Oscar HDM PYROX SYN Complex Moly EP 0 specifically designed for the lubrication of extra heavy-duty off-highway and mining equipment.

APPLICATION

This lithium complex grease, containing 5% molybdenum disulfide, can be used in bucket pins, pivot pins and highly loaded chassis components, central lubrication systems for heavy equipment and for general purpose chassis lubrication.

PROPERTIES

- High performance at high and low temperatures provides protection at high temperatures and low torque, easy starts at low temperatures.
- Highly effective rust and corrosion protection ensures high performance in wet environments, reducing downtime and reducing maintenance costs.
- Effective extreme pressure and anti-wear properties enhance bearing protection in difficult operating conditions, reducing downtime and reducing maintenance costs

TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	OSCAR HDM PYROX SYN Complex Moly EP 0
Soap/Thickener			Lithium Complex
Base oil			Synthetic
NLGI Grade	ASTM D217	-	0
Color	Visual		Black
Molybdenum Disulfide Content		wt%	5
Four ball Extreme Pressure Test, Weld Point, kgf	ASTM D2596	kgf	500
Penetration 60X, 0.1mm	ASTM D217		357
Dropping point, °C	ASTM 2265	°C	223
Kinematic viscosity of the base oil @ 40°C, mm ² /s	ASTM D445	mm ² /s	68

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.oscarlubricants.com