



PRODUCT DATA SHEET

Oscar Zircon Novus 15W40 CK-4/SN

Synthetic based multi grade diesel engine oil.

DESCRIPTION

Oscar Zircon Novus is an advanced part-synthetic heavy duty engine oil. Conforming to the requirements of PC-11 engine oil technology, it can be used in diesel engines where API CK-4 or, CJ-4 and below is required. Specifically engineered to deliver longer oil life, enabling longer service intervals even under severe operating conditions.

PROPERTIES

This lubricant assures:

- superior thermo-oxidative stability
- higher level of protection against soot-related viscosity increase and viscosity loss
- Excels under high pressure

APPLICATIONS

- Formulated for modern, technically advanced diesel engines used in city and suburban driving conditions.
- Designed to endure extreme conditions (heat, load, speed)
- API CK-4/SN, E6/E9/E7-16 228.51/M3477/MTU 3.1/DQC IV-10LAECF-3/VDS 4.5/VDS 4/CES 20081/CES 20086/DDC 93K222M3677 & Scania in progress

TYPICAL PROPERTIES

Oscar Zircon Novus		
Typical Properties	SAE Grade	15W40
	API level	CK-4/SN
Test Parameters	ASTM Method	Typical Values
Density @ 15°C, kg/l	ASTM D1298	0.88
Viscosity @ 100°C, cSt	ASTM D445	15.5
Viscosity @ 40°C, cSt	ASTM D445	116
Viscosity Index	ASTM D2270	140
Flash Point, °C	ASTM D92	228



BN, mg KOH/g	ASTM D2896	10
Pour Point , °C	ASTM D97	-42

January 2022

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice.