

## PRODUCT DESCRIPTION

**Oscar Jade Gold OEM Specific 5W30** is a synthetic engine oil for gasoline and diesel passenger's cars engines, particularly suitable for turbo compressed, multi-valve and direct injection diesel engines. Oscar Jade Gold can be used in the most difficult operating conditions (motorways, dense urban traffic...), and is appropriated for all driving types.

## APPLICATION

This product meets or exceeds the requirements ACEA A5/ B5 specifications for petrol engine oils, as well as the requirements of many major American, and European engine manufacturers.

## PROPERTIES

- Quick cold weather starting and fast protection helps to extend engine life
- Excellent overall lubrication and wear protection performance
- Helps to reduce oil aging resulting in long lasting protection

## PERFORMANCE LEVELS

Meets and exceeds:

API SN, SL/CF; ACEA A5/B5; FORD WSS-M2C913-D; FORD WSS-M2C913-C; FORD WSS-M2C913-B; FORD WSS-M2C913-A; VOLVO VCC 95200377; MB 229.6; FIAT 9.55535-G1; JAGUAR STJLR.03.5003; LAND ROVER STJLR.03.5003

## TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	OSCAR JADE GOLD
Viscosity Grade			5W30
Density @ 15°C	ASTM D1298	kg/l	0.854
Viscosity @ 100°C	ASTM D445	cSt	10
Viscosity @ 40°C	ASTM D445	cSt	55
Viscosity Index (min)	ASTM D2270	-	≥50
Cold Crank Simulator	ASTM D5293	cP	<6,600 @ -30 °C
Pour Point	ASTM D97	°C	-36
Flash Point	ASTM D92	°C	>230
Total Base Number (TBN)	ASTM D2896	mg KOH/g	8

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice

## HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website [www.oscarlubricants.com](http://www.oscarlubricants.com)