

Oscar HDM NCEO XT 40

PRODUCT DESCRIPTION

Premium CNG/LNG oil formulated to deliver outstanding protection and long drain performance in a wide variety of compressed natural gas (CNG), liquefied natural gas (LNG) and liquefied petroleum gas (LPG) stationary engine applications. It is a medium ash (0.5 wt. %) lubricant giving optimum performance in engines fueled by natural gas.

PROPERTIES

This lubricant assures:

- Alternative fuel performance:
- Great performance for medium and heavy-duty engines using CNG, LNG or LPG.
- Excellent engine cleanliness
- Sludge control; and valve, or piston deposits in field trials and engine tests.
- Oil oxidation/nitration control

PERFORMANCE LEVELS

Meets the requirements:

CAT 3516TA LE/ natural gas and landfill
 CAT G3516TA LE/ natural gas and landfill
 INNIO Jenbacher Series 3 (Class B fuel gas)
 INNIO Jenbacher JGS 320 (Class A fuel gas)
 Waukesha VHP L7042GL, VHP 5904LTD/ natural gas
 Wartsila 20V34SG/ natural gas (sweet gas)

TYPICAL PROPERTIES

Oscar HDM NCEO XT		
Typical Properties	SAE Grade	40
	API level	CF
Test Parameters	ASTM Method	Typical Values
Density @ 15°C, kg/l	ASTM D1298	0.880
Viscosity @ 100°C, cSt	ASTM D445	13.5
Flash Point, °C	ASTM D92	255
BN, mg KOH/g	ASTM D2896	6.5
Pour Point, °C	ASTM D97	-25
Sulphated ash, wt. %	ASTM D874	0.50

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.oscarlubricants.com