

Oscar HDM Compressor Oil

PRODUCT DESCRIPTION

Oscar HDM Compressor Oils are designed for compressor systems employing gears and bearings, and are highly recommended for crankcases. They are formulated with high-quality mineral base oils and a high-performance additive system to provide exceptional equipment protection and reliability for compressors operating under mild to severe conditions.

APPLICATION

Oils for all highly-stressed air compressors which require a VCL/VDL oil with DD additives for good dirt dislodging and dirt transportation. Oscar Lubricants can offer the best Compressor oil for your specific application

PROPERTIES

- Longer running periods between maintenance intervals
- Improved valve performance
- Lower maintenance costs

PERFORMANCE LEVELS

Meets and exceeds:

VCL/VDL air compressor oils according to DIN 51 506

TYPICAL PROPERTIES

PARAM ETERS	TEST M ETHOD	UNIT	OSCAR HDM COM PRESSOR OIL	
Product Name			100	150
Density at 15 °C	ASTM D1298	kg/m ³	0.875	0.865
Flash point Cleveland, min.	ASTM D92	°C	250	260
Kinematic viscosity at 40 °C	ASTM D445	mm ² /s	105	145
Kinematic viscosity at 100 °C	ASTM D445	mm ² /s	11.5	14.5
Viscosity Index	ASTM D2270	-	100	100
Pour Point	ASTM D97	°C	-25	-25

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.oscarlubricants.com