

Oscar HDM TFX 50 TO-4

PRODUCT DESCRIPTION

Oscar HDM TFX 50 TO-4 is an extra high-performance, heavy-duty transmission and drive-train lubricants engineered to meet or exceed the requirements of the rigorous Caterpillar TO-4 specification. This product line is uniquely designed to optimize the performance of powershift transmissions, gearboxes, and final drives. In hydraulic applications, they provide maximum protection even in high pressure systems

APPLICATION

- Heavy duty transmissions, gear boxes, final drives, and hydraulic systems used in off-highway applications
- Off-highway industries including: mining, construction, quarrying, and agriculture
- Manual, powershift, and automatic transmissions where Allison C-4 fluids are called for including Twin Disc and transmissions calling for Type F fluids
- Most mobile equipment hydraulic applications

PROPERTIES

This lubricant assures:

- Optimized clutch-friction retention and slippage control
- Compatible with modern clutch materials and elastomers
- Longer clutch life and higher performance
- Increased levels of anti-wear and load carrying capability
- Reduced gear wear and extended life in transmissions, gearboxes, and final drives
- Excellent foam control protection
- Top performance in wet brakes; excellent control of brake chatter
- Excellent thermal and oxidation stability
- Outstanding hydraulic oil stability and protection against high-pressure pump wear

TYPICAL PROPERTIES

Oscar HDM TFX 50 TO-4		
Typical Properties	SAE Grade	50
Test Parameters	ASTM Method	Typical Values
Density @ 15°C, kg/l	ASTM D1298	0.90
Viscosity @ 100°C, cSt	ASTM D445	18.0
Viscosity @ 40°C, cSt	ASTM D445	195
Viscosity Index	ASTM D2270	100
Flash Point, °C	ASTM D92	245
Pour Point, °C	ASTM D97	-16

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.oscarlubricants.com